

CS-2511WES THE BEST POWER TO WEIGHT RATIO WITH REAR HANDLE







^{* 5} Year domestic warranty /2 year commercial warranty not available in all markets. Check with your dealer for details.



FEATURES & BENEFITS



DEBRIS SHIELD AS OPTION SNOW SHIELD AS OPTION

Engine	Dry Weight* (kg)	Output	Fuel Tank	Oil Tank	Guide Bar	Saw Chain Pitch	Gauge
Displacement (cm³)		(kW/ps)	Capacity (L)	Capacity (L)	Length (cm)	(inch)	(inch)
25.0	2.6	1.1/1.5	0.19	0.14	20,25,30	20,25: 1/4 30: 3/8	20,25: 0.043 30: 0.050

*withoutguidebar&sawchain

- // 25.0cm³ professional-grade, 2-stroke engine provides impressive cutting performance.
- // Ultra light weight reduces operator fatigue.
- // Compact design enables operators to maneuver in tight spaces.
- // ES-start for easier starting.
- // G-Force Engine Air Pre-Cleaner reduces engine exposure to dirt and debris for less maintenance and longer life.
- // Oiler adjustment on top enables operator to control oil flow for optimal operation.
- // Palm rest for maneuverability and precise control.
- // Starter grip can be used to open the caps manually.
- // Wide tank openings for easy oil/fuel refilling.
- // Meshed louvers to prevent pine needle penetration.
- // Debris shield as an option prevents debris penetration.
- // Snow shield as an option prevents snow penetration.











Specifications, descriptions, and illustrative materials in this literature are as accurate as known at the time of publication, but are subject to change without notice.

